

塑料电缆防水接头

材料：尼龙(PA66)

夹紧件：尼龙(PA66)

密封件：丁腈橡胶(NBR)

O型密封圈：丁腈橡胶(NBR)

防护等级：IP67

环境温度：-40~100°，短时 120°



产品型号	螺纹规格	适用电缆直径 (mm)	螺纹外径 (mm)	螺纹长度 (mm)
PG7	PG7	4~7	12	9
PG9	PG9	5~8	16	9
PG11	PG11	6~10	18	9
PG13.5	PG13.5	7~12	20	9
PG16	PG16	8~14	22	10
PG21	PG21	13~18	27	10
PG25	PG25	16~21	29	10
PG29	PG29	18~25	35	13.5
PG36	PG36	24~32	47.5	20
PG42	PG42	31~41	54	19
PG48	PG48	35~45	58	22
PM12	M12x1.5	3~6	12	13.5
PM16	M16x1.5	4~8	16	8.5
PM18	M18x1.5	5~10	18	8.5
PM20	M20x1.5	6~11	20	9
PM22	M22x1.5	8~13	22	10.5

金属电缆防水接头


材料：黄铜镀镍

密封件：丁腈橡胶(NBR)

O型密封圈：丁腈橡胶(NBR)

防护等级：IP67

环境温度：-40~100°，短时 120°



产品型号	螺纹规格	适用电缆直径 (mm)	螺纹外径 (mm)	螺纹长度 (mm)
PTM12	M12x1.5	3~6	12	5.5
PTM16	M16x1.5	4~8	16	7
PTM18	M18x1.5	5~10	18	7
PTM20	M20x1.5	6~11	20	7.5
PTM22	M22x1.5	8~13	22	8